

## B26-E Double Rough Surfacacer



# **Specifications**

## **CAPACITY**

Thickness: 5/8" - 4"

- Width: 24" (30" optional)
- Length: 51" Min. self-feed
- Weight: 14,000 lbs.
- Vacuum:
  - 24"- (2) 9" dia. pipe, 5400 CFM
  - 30"- (2) 10" dia. pipe, 6600 CFM

## **HORSEPOWER**

- Top: 75 HP
- Bottom: 40 HP
- Hydraulic unit: 3 HP

## **FEED SYSTEM**

- Electric-drive (2) 15 HP
- Feed speed:
  - 75 - 300 FPM
  - 125-400 FPM Option
- Upper rolls:
  - 16" diameter air filled tires
  - Electric drive
  - Hydraulically tensioned
- Lower rolls:
  - 12" diameter non-powered,
  - Idler type, and reversible

## **CUTTERHEADS**

- 8" diameter cutting circle - 3600 RPM
- Up to 12 knives (straight)
- Up to 8 row carbide spiral bits (optional)

## **CONSTRUCTION**

- Steel fabricated frame
- Thermally stress-relieved

## **STANDARD EQUIPMENT**

- Anti-lap bar device
- Air tensioned/released chipbreaker
- LCD digital positioner - top head
- Built-in top and bottom jointers with "safestone" advance
- Hydraulic top and bottom head locks
- Top and bottom dust hoods
- Electrically interlocked safety guards with easy access
- Quick release pressure bar
- Electrical panel
- Free standing operator's console with FPM readout

- Hosing and electrical runs

#### **OPTIONAL EQUIPMENT**

- Automated bottom head traverse
- Automated top head hoist
- Automated pressure bar control
- Automated set works - top head
- Powered bottom rolls
- Non-marking outfeed tires
- Thin stock control
- Small remote operator's station
- Chrome wear parts
- Electric powered infeed conveyor